4 CH AHD + 1 CH IP Hybrid DVR

SA-4050AHD-2 (MMA)

720P 1080P 1080P





MODEL			SA-4050AHD-2 (MMA)
System		Compression Format	High profile H.264
		ONVIF	Yes
		Format	AHD/CVBS
Video		Input	4CH AHD Standard BNC + 1CH IP (Over Network)
		Standard Output	HDMI, VGA (800x600, 1024x768, 1280x1024), CVBS
Audio		Input	4CH
		Output	1CH
		Two Way Audio	Yes
Recording	AHD	Real-Time Recording	4CH 1080P Half Real-Time
		2MP (1080P)	60FPS (NTSC)/50FPS (PAL) Total. Up to 15/12FPS Per Channel
		1MP (720P)	120FPS (NTSC)/100FPS (PAL)
	Analog	Real-Time Recording	4CH 960H Real-Time
		960H	120FPS (NTSC)/100FPS (PAL)
		D1	No
		CIF	No
	IP	Real-Time Recording	1CH 1080P Real-Time
		3MP	No
		2MP (1080P)	30FPS (NTSC)/25FPS (PAL)
		1.3MP (960P)	30FPS (NTSC)/25FPS (PAL)
		1MP (720P)	30FPS (NTSC)/25FPS (PAL)
	General	Recording Modes	Schedule, Manual, Motion, Sensor
Playback		AHD/CVBS Playback	4CH
		IP Playback	1CH
		Search Mode	Time, Event, File Management
Backup		USB	2 USB 2.0 Port
		DVD Burner	No
		Backup Format	AVI/DAT
Remote Application		AHD Stream	Master Stream 1-25/30FPS@720P / 1-12/15FPS@1080P; Sub-Stream: Up to 1-25FPS@720P
		Analog Stream	Master Stream 1-25/30FPS@960H; Sub-Stream Up to 1-25FPS@960H
		IP Stream	Master Stream 1-25/30FPS@1080P; Sub-Stream Up to 1-25/30FPS@D1
		Master Stream	Up to 4Ch@Recording Resolution
		Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8)
		CMS	Yes
		Mobile Application	ProvisionCAM for iPhone/Android; ProvisionHD for iPad/Android Tablet
		User Access	10 Users Online with Professional Autorithy Management
Alarm		Input	4CH
		Output	1CH
Storage		HDD	1 SATA (4TB)
		E-SATA	No
PTZ		Connection	RS-485
		Supported Protocols	Pelco D, Pelco P, Samsung, Visca, ONVIF, CoC
		Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
Network		Ethernet	100 Mbps (RJ-45)
		Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P
Others		Dimention	W255xD200xH43mm
		IR Controller	Yes
		Power Supply	12V/2A
		Operation Temperature	0°C ~50°C